

CHINTAN ENGINEERS

29, BHAGIRATH INDUSTRIAL ESTATE PART-1, NAGARVEL HANUMAN ROAD,
AMRAIWADI, AHMEDABAD-380026 INDIA
CONTACT NO. : +91-9824970261, +91-9974192731
E-MAIL: CHINTANENGINEERS24@GMAIL.COM
WEB: WWW.CHINTANENGINEERS.COM

Diesel Flow Meter (CE-122)

We are pleased to introduce our new “ACHIEVERS” positive displacement flow meters kerosene or any slightly viscous non corrosive liquids; this is reset type, mechanical flow meters

Application

Oval Gear Flow meter is a kind of positive displacement meter to measure the liquid flow or instantaneous flow of the pipe tube. It is a kind of accumulate meter. With characteristics of high accuracy, small change by the fluid viscosity, it is widely used to measure oil kind liquid, forbidden to measure corrosive

Working Principle

The measurement part of oval gear flow meter is posed by two elliptical gears mesh with each other and its shell (measuring room). The flow meter works by two elliptical gears to mesh with each other, its working process are as follows: the pressure of liquid from inlet side, to show the outlet pressure, the bottom rotor has no rotating torque even it effected the liquid pressure, but the above gears will move by the rotating pressure .In the status of the above gears driving gear, and the bottom gear is driven gear. both of these two gears have rotating torque by the liquid pressure, and they move with the direction of the arrow to space The gear space is opposite to, the bottom gear is driving gear, and above gear is driven gear. The bottom gear pushes the liquid out from the halfmoon space under the liquid press pushes liquid volume four times of “measurement room”. So, as long as the rotation of gears, the liquid volume can be counted



Techical Details :

Size	4" Or 100 mm
Color	Green
Flow Range	160~1600L/min
Accuracy	+/- 0.2% OR +/-0.5%
Repeatability	+/-0.03%
Operating Pressure	1.8 Mpa
Material	Iron