

CHINTAN ENGINEERS

29, BHAGIRATH INDUSTRIAL ESTATE PART-1, NAGARVEL HANUMAN ROAD,
AMRAIWADI, AHMEDABAD-380026 INDIA
CONTACT NO. : +91-9824970261, +91-9974192731
E-MAIL: CHINTANENGINEERS24@GMAIL.COM
WEB: WWW.CHINTANENGINEERS.COM

Fuel Pump

1) CE-40DC Fuel Pump



Technical specifications :-

CAST IRON PUMP BODY FINISHED WITH ANTI-CORROSION PAINT.

VANE PUMP WITH SINTERED STEEL ROTOR AND ACETAL RESIN VANES.

BY-PASS VALVE INCORPORATED IN THE PUMP BODY.

DIRECT CURRENT BRUSH MOTOR WITH PERMANENT MAGNET STATOR.

MOTOR PROTECTION GRADE IP55.

USED IN INTERMITTENT SERVICE WITH 30 - MINUTE WORK CYCLES.

FLOWRATE:40L / MIN

22A(12V),12A(24V)

2800RPM

USAGE:DIESEL,KEROSENE

IN/OUT LET:3 / 4"

G.W:3.5KGS

N.W:3KGS

2) ***CE-70-A-DC Fuel Pump***



TECHNICAL DETAILS :-

VOLTAGE : 12V/24V

CURRENT : 4A

INPUT/OUTPUT : 3/4”

FLOWRATE : 70L/MIN

HEAD : 10M

SUCTION : 2-4 M

3) ***CE-80-DC FUEL PUMP***



TECHNICAL DETAILS :-

DISPLACEMENT, SELF-PRIMING, ROTARY ELECTRIC VANE PUMPS FOR TRANSFERRING DIESEL FUEL, CHARACTERIZED BY HIGH FLOWRATE. ALL PUMPS ARE EQUIPPED WITH BY-PASS VALVE.POWERFUL, DEPENDABLE AND ECONOMICAL, THEY ARE AVAILABLE IN 12 AND 24 -VOLT VERSIONS. THANKS TO THEIR COMPACT SIZE, EASE OF INSTALLATION, DEPENDABILITY AND SAFETY, THESE PUMPS ARE USED AS THE PRIMARY SYSTEM ON EARTH-MOVING MACHINERY AND ON MOBILE FUEL PUMPS ON VEHICLES OR IN CONSTRUCTION YARDS.

FLOWRATE : 80L/MIN

INPUT/OUTPUT:1 INCH

CURRENT:44A/12V,21A/24V